

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product form : Mixture  
 Trade name : Foam-Lok LPA 3500  
 Product code : LPA 3500 - All Grades  
 Other means of identification : LPA 3500 – FoamLok Resin – All Grades  
 Urethane System Resin Component, B – Component,B – Side, Polyol Resin

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Two-Component, closed-cell, polyurethane foam system specifically designed to provide a high performance, light weight roofing system for use over insulation water proofing a wide variety of roof deck construction and configurations.  
 Use of the substance/mixture : A component for the production of spray insulation foam

**1.3. Details of the supplier of the safety data sheet**

Huntsman Building Solutions  
 3315 E. Division Street,  
 Arlington, TX 76011  
 Tel: 817-640-4900 , 888-224-153  
 sdsinfo@huntsmanbuilds.com

**1.4. Emergency telephone number**

Emergency number : CARECHEM (866) 928-0789

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**GHS-US classification**

Acute Tox. 4 (Oral) H302  
 Skin Corr. 1B H314  
 Eye Dam. 1 H318

**2.2. Label elements**

**GHS-US labelling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger  
 Hazard statements (GHS-US) : H302 - Harmful if swallowed  
 H314 - Causes severe skin burns and eye damage  
 H318 - Causes serious eye damage  
 Precautionary statements (GHS-US) : P260 - Do not breathe mist, spray, vapours, fume, gas, dust  
 P264 - Wash hands, face thoroughly after handling  
 P270 - Do not eat, drink or smoke when using this product  
 P280 - Wear eye protection, protective gloves, protective clothing  
 P301+P312 - If swallowed: Call a POISON CENTER if you feel unwell  
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P310 - Immediately call a doctor, a POISON CENTER  
 P321 - Specific treatment (see on this label)  
 P330 - Rinse mouth  
 P363 - Wash contaminated clothing before reuse  
 P405 - Store locked up  
 P501 - Dispose of contents/container to comply with applicable local, national and international

regulation.

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity (GHS-US)**

No data available

**SECTION 3: Composition/information on ingredients**

**3.1. Substance**

Not applicable

**3.2. Mixture**

Name	Product identifier	%	GHS-US classification
Oxirane, methyl-, polymer with oxirane, ether with 2,6-bis[[bis(2-hydroxyethyl)amino]methyl]-4-nonylphenol (5:1)	(CAS No) 52019-35-9	<30	Skin Irrit. 2, H315 Eye Dam. 1, H318
2-Propanol, 1-chloro-, phosphate (3:1)	(CAS No) 13674-84-5	<20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312
1-Propanol, 2,2-dimethyl-, tribromo derivative	(CAS No) 36483-57-5	<10	Eye Irrit. 2A, H319
Nonylphenol ethoxylates	(CAS No) 9016-45-9	<10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Triethyl phosphate	(CAS No) 78-40-0	<7.5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
1,3-Propanediamine, N,N-bis[3-(dimethylamino)propyl]-N',N'-dimethyl-	(CAS No) 33329-35-0	<7	Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318
Diethylene glycol	(CAS No) 111-46-6	<6	Acute Tox. 4 (Oral), H302
Ethylene glycol	(CAS No) 107-21-1	< 4.3	Acute Tox. 4 (Oral), H302
Bis(2-dimethylaminoethyl) ether	(CAS No) 3033-62-3	<5	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- First-aid measures general : In all cases of doubt, or when symptoms persist, seek medical attention.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of breathing difficulties administer oxygen. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical advice.
- First-aid measures after skin contact : Remove contaminated clothing immediately. Wash skin thoroughly with mild soap and water. Seek medical attention immediately.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Contact lenses should be removed. Immediately get medical attention.
- First-aid measures after ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Call a POISON CENTER or doctor/physician. Give water to drink if victim completely conscious/alert. Never give anything by mouth to an unconscious person. Seek medical attention immediately. If unconscious, place in the recovery position and seek medical advice.

**4.2. Most important symptoms and effects, both acute and delayed**

- Symptoms/injuries : Causes severe skin burns and eye damage.
- Symptoms/injuries after inhalation : Inhalation of mist or aerosol may cause irritation to nose, throat and the respiratory tract.
- Symptoms/injuries after skin contact : Causes severe skin burns and eye damage. Corrosive to eyes and skin.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : Harmful if swallowed. Gastrointestinal tract discomfort may produce nausea and vomiting. At levels above the recommended exposure limit, the fluorocarbon acts as a weak narcotic. Acute overexposure causes tremors, confusion, irritation, suffocation, and may result in cardiac sensitization.

**4.3. Indication of any immediate medical attention and special treatment needed**

No additional information available

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

Suitable extinguishing media : Water spray. Dry extinguishing powder. Carbon dioxide. Foam.  
 Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture**

No additional information available

**5.3. Advice for firefighters**

Protective equipment for firefighters : Use self-contained breathing apparatus and chemically protective clothing.  
 Other information : Prevent entry to sewers and public waters.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

General measures : Stop leak if safe to do so. Spills of this product present a serious slipping hazard. Avoid breathing mist or vapor . Avoid contact with skin, eyes and clothing.

**6.1.1. For non-emergency personnel**

Protective equipment : Wear suitable protective clothing. Refer to section 8.

**6.1.2. For emergency responders**

Protective equipment : Equip cleanup crew with proper protection.  
 Emergency procedures : Ensure adequate ventilation.

**6.2. Environmental precautions**

Prevent entry to sewers and public waters. If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.

**6.3. Methods and material for containment and cleaning up**

Methods for cleaning up : Take up liquid spill into inert absorbent material. Sweep or shovel spills into appropriate container for disposal. Ensure all national/local regulations are observed.

**6.4. Reference to other sections**

Refer to sections 8 and 13.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Precautions for safe handling : Avoid mixing with air or use for any purpose above atmospheric pressure . Product should not be mixed with air above atmospheric pressure for leak testing or any other purpose. Use dry nitrogen to transfer or leak test equipment pressurized with product.  
 Hygiene measures : Wash contaminated clothing prior to re-use. Always wash hands and face immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke when using this product.

**7.2. Conditions for safe storage, including any incompatibilities**

Technical measures : Provide local exhaust or general room ventilation. A washing facility/water for eye and skin cleaning purposes should be present.  
 Storage conditions : Keep out of direct sunlight. Store in original container. Keep container tightly closed in a cool, well-ventilated place. Keep away from heat. Do not freeze. Product that is frozen and/or tending to sedimentation can be liquefied or homogenized by careful application of indirect heat (do not use flames or direct contact with a heat source). Protect from moisture.  
 Incompatible materials : Keep away from strong acids, strong bases and oxidizing agents.  
 Storage temperature : 21 - 26 °C ( 70 - 80 °F )

**7.3. Specific end use(s)**

No additional information available

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

<b>Ethylene glycol (107-21-1)</b>		
USA ACGIH	ACGIH Ceiling (mg/m³)	100 mg/m³

Bis(2-dimethylaminoethyl) ether (3033-62-3)		
USA ACGIH	ACGIH TWA (ppm)	0.05 ppm
USA ACGIH	ACGIH STEL (ppm)	0.15 ppm

### 8.2. Exposure controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



- Hand protection : Wear suitable gloves resistant to chemical penetration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
- Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.
- Skin and body protection : Wear protective clothing.
- Respiratory protection : Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Colour : Dark orange to brown
- Odour : Amine-like
- Odour threshold : No data available
- pH :  $\geq 7$
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point :  $> 200$  °C (closed cup)
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapour pressure : No data available
- Relative vapour density at 20 °C : No data available
- Relative density : No data available
- Density : 1.15 - 1.17 g/cm<sup>3</sup> @ 25°C (Bulk Density)
- Solubility : Water: Slightly soluble
- Log Pow : No data available
- Log Kow : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : 800 - 1000 mPa.s @ 23 °C
- Explosive properties : No data available
- Oxidising properties : No data available
- Explosive limits : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable under use and storage conditions as recommended in section 7.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Temperatures above 26 °C (80 °F) . Moisture. Direct sunlight. Heat.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids, bases.

### 10.6. Hazardous decomposition products

Toxic fumes. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. unburned hydrocarbons. possibly carbonyl fluoride. hydrogen fluoride.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

<b>Foam-Lok LPA 2800</b>	
ATE US (oral)	500.00000000 mg/kg bodyweight
<b>Ethylene glycol (107-21-1)</b>	
LD50 oral rat	4000 mg/kg
ATE US (oral)	500.00000000 mg/kg bodyweight
<b>2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)</b>	
LD50 oral rat	930 (930 - 1550) mg/kg
LD50 dermal rabbit	1230 mg/kg
LC50 inhalation rat (mg/l)	> 17.8 mg/l (Exposure time: 1 h)
ATE US (oral)	930.00000000 mg/kg bodyweight
ATE US (dermal)	1230.00000000 mg/kg bodyweight
<b>Bis(2-dimethylaminoethyl) ether (3033-62-3)</b>	
LD50 oral rat	910 mg/kg
LD50 dermal rabbit	238 mg/kg
LC50 inhalation rat (ppm)	117 ppm (Exposure time: 6 h)
ATE US (oral)	910.00000000 mg/kg bodyweight
ATE US (dermal)	238.00000000 mg/kg bodyweight
ATE US (gases)	4500.00000000 ppmv/4h
ATE US (vapours)	11.00000000 mg/l/4h
ATE US (dust,mist)	1.50000000 mg/l/4h
<b>Nonylphenol ethoxylates (9016-45-9)</b>	
LD50 oral rat	2590 mg/kg
LD50 dermal rabbit	1780 µl/kg
ATE US (oral)	2590.00000000 mg/kg bodyweight
<b>Triethyl phosphate (78-40-0)</b>	
LD50 oral rat	1100 - 1600 mg/kg
ATE US (oral)	1100.00000000 mg/kg bodyweight
<b>1,3-Propanediamine, N,N-bis[3-(dimethylamino)propyl]-N',N'-dimethyl- (33329-35-0)</b>	
ATE US (dermal)	1100.00000000 mg/kg bodyweight
<b>Diethylene glycol (111-46-6)</b>	
LD50 oral rat	12565 mg/kg
LD50 dermal rabbit	11890 mg/kg

<b>Diethylene glycol (111-46-6)</b>	
ATE US (oral)	500.00000000 mg/kg bodyweight
ATE US (dermal)	11890.00000000 mg/kg bodyweight
Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: >= 7
Serious eye damage/irritation	: Causes serious eye damage. pH: >= 7
Respiratory or skin sensitisation	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Symptoms/injuries after inhalation	: Inhalation of mist or aerosol may cause irritation to nose, throat and the respiratory tract.
Symptoms/injuries after skin contact	: Causes severe skin burns and eye damage. Corrosive to eyes and skin.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Harmful if swallowed. Gastrointestinal tract discomfort may produce nausea and vomiting. At levels above the recommended exposure limit, the fluorocarbon acts as a weak narcotic. Acute overexposure causes tremors, confusion, irritation, suffocation, and may result in cardiac sensitization.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Ethylene glycol (107-21-1)</b>	
LC50 fishes 1	41000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	46300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	14 - 18 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)</b>	
LC50 fishes 1	56.2 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	63 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 1	45 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
LC50 fish 2	180 mg/l (Exposure time: 96 h - Species: Leuciscus idus [static])
EC50 other aquatic organisms 2	4 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
<b>Diethylene glycol (111-46-6)</b>	
LC50 fishes 1	75200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	84000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>Ethylene glycol (107-21-1)</b>	
Log Pow	-1.93
<b>2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)</b>	
BCF fish 1	1.9 - 4.6
Log Pow	2.59

<b>Triethyl phosphate (78-40-0)</b>	
Log Pow	0.8 - 1.11
<b>Diethylene glycol (111-46-6)</b>	
BCF fish 1	100 - 180
Log Pow	-1.98 (at 25 °C)

**12.4. Mobility in soil**

No additional information available

**12.5. Other adverse effects**

Effect on ozone layer : No additional information available  
 Effect on the global warming : No additional information available

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Product wastes can often be incinerated in approved facilities. Consult the appropriate authorities about waste disposal.

Additional information : Do not re-use empty containers. Do not dispose of waste into sewer. Do not cut, grind, drill, weld, reuse or dispose off containers unless adequate precautions are taken against these hazards.  
 Container Disposal: Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Refer to 40 CFR § 261.7 (residues of hazardous waste in empty containers). Decontaminate containers prior to disposal. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. Ensure all national/local regulations are observed.

Ecology - waste materials : Avoid release to the environment. Do not allow into drains or water courses.

**SECTION 14: Transport information**

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s., 8, II

UN-No.(DOT) : 1760

DOT NA no. : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

Department of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name (Polyol Resin Blend)

Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.  
 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
 T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)  
 TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.  
 TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

**Additional information**

Other information : No supplementary information available.

**ADR**

Transport document description : No additional information available

**Transport by sea**

UN-No. (IMDG)	: 1760
Proper Shipping Name (IMDG)	: CORROSIVE LIQUID, N.O.S.
Class (IMDG)	: 8 - Corrosive substances
Packing group (IMDG)	: II - substances presenting medium danger

**Air transport**

No additional information available

**SECTION 15: Regulatory information**

**15.1. US Federal regulations**

<b>Ethylene glycol (107-21-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	5000 lb
SARA Section 313 - Emission Reporting	1.0 %

<b>Diethylene glycol (111-46-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

**15.2. International regulations**

**CANADA**

<b>Ethylene glycol (107-21-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

<b>Nonylphenol ethoxylates (9016-45-9)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

<b>Diethylene glycol (111-46-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects

**EU-Regulations**



**Ethylene glycol (107-21-1)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

No additional information available

**Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]**

No additional information available

**15.2.2. National regulations**

**Ethylene glycol (107-21-1)**

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Canadian IDL (Ingredient Disclosure List)

**15.3. US State regulations**

No additional information available

**SECTION 16: Other information**

- Indication of changes : 3. Composition/information on ingredients. 2.1. Classification of the substance or mixture according to the federal final rule of hazard communication revised on 2012 (HazCom 2012).
- Revision date : 11/4/2014 12:00:00 AM
- Sources of Key data : Data sources: SDS - Safety Data Sheet.
- Abbreviations and acronyms : CAS - Chemical Abstracts Service. CSR - Chemical Safety Report. EC - European Community. EEC - European Economic Community. MSDS - Material Safety Data Sheet. PBT - Persistent, Bioaccumulative and Toxic substance. SDS - Safety Data Sheet . STEL- Short-Term Exposure Limit . TLV- Threshold Limit Value. TWA- Time Weighted Average. vPvB - Very Persistent and Very Bioaccumulative.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled

SDS US (GHS HazCom 2012)

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY HUNTSMAN BUILDING SOLUTIONS. HEREUNDER ARE GIVEN GRATIS AND HUNTSMAN BUILDING SOLUTIONS ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. HUNTSMAN BUILDING SOLUTIONS WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.